

Self-build sound-isolation booths

Affordable, flexible and incredibly easy to build
– without compromising on acoustics

Technical information

STUDIOBRICKS Soundproof Modules

Size

- Many size options are available; can accommodate anything from a solo musician to a large group/band or choir
- Typical internal ceiling height is 2040mm

Performance

- Typical sound insulation performance for the Standard booth is 46dB, tested in accordance with ISO 717-1
- Typical sound insulation performance for the Pro booth is 52dB, tested in accordance with ISO 717-1

Flexibility

- Modular panel design provides a large selection of different size cabins
- Easy re-location of existing cabins

Construction

- Modular, interlocking sound-isolating panels are secured with sound-isolating battens
- Acoustically sealed base channel controls wall panel placement
- Painted panel finish. Painted white as standard (other colours and designs are available on request)
- Typical panel weight would be nominally 32kgs/m²
- Full length acoustically engineered glass door with acoustic seals

Ventilation

- Integral fan unit supplied as standard
- Acoustically isolated HVAC connections are also available

Registered address:

Festival House, 4 Chapman Way, Tunbridge Wells,
Kent, TN2 3EF, United Kingdom

Tel: +44 (0)1892 619719 | Freephone: 0800 072 7799

Email: sales@blackcatmusic.co.uk | www.blackcatmusic.co.uk



Exclusive UK Providers Of...



Electrical components

- Rooms come with led lighting as standard
- Client's own electrical cables can be fed into the cabin via a cable port
- Additional surface fixed lighting is available if required
- Additional safety items such as fire alarm detectors, sounders and strobe lights can be installed within the rooms (additional works by incumbent suppliers may be required)

Installation requirements

- Minimum clearance over room height is 200mm
- Minimum spacing of 50mm from walls and 250mm from adjacent cabins
- Supporting floor structures will accommodate the room loadings, be flat, level and true
- Floor level tolerance provides a minimum flat and level surface of 3mm over 1000mm
- Ventilation of the room where the cabin is located is required
- The cabin is designed for self-build
- Installation service (if required) demands room to be cleared of furniture prior to the arrival of our installation team
- Site inspection may be required by our staff, before delivery/installation schedule is agreed

Options and additions

- Closure panels between and around cabins
- Glazed acoustically engineered windows available for control room purposes, observation, security or to provide natural light
- Rooms come with cable ports as standard. Additional sockets, data points etc are available within three-compartment dado trunking, should this be required
- Cabins come with sound isolating floating floors as standard
- Sound limiting devices available for fitting in accordance with BB93 and/or Health and Safety requirements
- Locking door with internal lock override available on request
- Surface fixed lighting available
- Additional safety items such as fire alarm detectors, sounders and strobe lights can be installed within the rooms (additional works by incumbent suppliers may be required)

Registered address:

Festival House, 4 Chapman Way, Tunbridge Wells,
Kent, TN2 3EF, United Kingdom

Tel: +44 (0)1892 619719 | Freephone: 0800 072 7799

Email: sales@blackcatmusic.co.uk | www.blackcatmusic.co.uk



Exclusive UK Providers Of...

studiobricks
Soundproof Modules